Product data sheet Characteristics

QO312L125G LOAD Center QO MLO 240V 125A 3PH 12SP

Product availability: Stock - Normally stocked in distribution facility



Price*: 332.00 USD



Main

Product or component type	Load Center
Range of product	QO
Load center type	Main lugs
Line Rated Current	125 A
Number of spaces	12
Short-circuit current	65 kA
Number of circuits	12
Number of tandem circuit breakers	0
Phase	3 phases
System Voltage	208Y/120 V AC 240/120 V delta AC 240 V delta AC

Complementary

	,	
NA -1 -		
Main	LeadOutle	
Product or component type	Load Center	
Range of product	QO	
Load center type	Main lugs	
Line Rated Current	125 A	
Number of spaces	12	
Short-circuit current	65 kA	
Number of circuits	12	
Number of tandem circuit breakers	0	
Phase	3 phases	
System Voltage	208Y/120 V AC 240/120 V delta AC 240 V delta AC	
Complementary AWG gauge	AWG 6AWG 2/0 (aluminium/copper)	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Order separately	
Electrical connection	Lugs	
Device composition	Grounding bar included (not installed)	
Electrical connection	Lugs	
Wiring configuration	3-wire 4-wire	
Material	Tin plated copper busbar	
Enclosure material	Welded sheet steel	
Surface finish	Baked enamel grey	
Box number	6	
Product certifications	UL listed	
Height	17.91 in (455 mm)	
<u> </u>	` '	

Width	14.25 in (362 mm)
-------	-------------------

Ordering and shipping details

Category	00011 - QO 3PH LOAD CENTER,INDOOR
Discount Schedule	DE3
GTIN	00785901295037
Nbr. of units in pkg.	1
Package weight(Lbs)	11.04000000000001
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1248 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months	